



REV.	DESCRIPTION	DATE
A/0	新版发行	2017.03.02
A/1	添加14、18、26孔	2017.03.02
A/2	添加2*8孔	2021.01.19

NOTES:

- MATERIAL SEE TABLE;
- PLATING SEE TABLE;
- RATING
- 3-1. OPERATING TEMPERATURE: -25~85°C
- 3-2. OPERATING VOLTAGE: 250V AC/DC
- 3-3. CURRENT RATING: 2AMPS(26#)
- 3-4. DIELECTRIC WITHSTANDING VOLTAGE: 1000V AC/Minute;
- 3-5. INSULATION RESISTANCE: 1000MΩ Min;
- 3-6. CONTACT RESISTANCE: 0.03Ω Max;
- PART NO. 61080-**02-5001

SERIES

CIRCUIT NO.

Packing Option:
0=Reel Packing

Lead Free & HF
5=Halogen-Free

Plating:
2=MATTE-TIN 80μ"Min
OVER Ni 30μ"Min.

CTK	dim A	dim B	dim C	dim D	dim E
14	12	14.7	22	17.7	18.7
16	14	16.7	24	19.7	20.7
18	16	18.7	26	21.7	22.7
20	18	20.7	28	23.7	24.7
24	22	24.7	32	27.7	28.7
26	24	26.7	34	29.7	30.7

序号	图号	名称	材料	数量	附注
3	122-1005-001	垫片 Fitting Nail	黄铜 brass	2	电镀(铜): 整个表面镀底镍30-120u"MIN,再镀亮镍80-180u"MIN..
2	112-1005-001	端子 Contact	黄铜 brass	N	电镀(铜): 整个表面镀底镍30-120u"MIN,再镀亮镍80-180u"MIN..
1	132-1005-001	基板 Housing	PA9T (UL94V-0)	1	本色

GENERAL TOLERANCES		DRAWN BY	赵博博/2017.03.02	 新富尔电子有限公司 XINFUER ELECTORN CO.,LTD	
0.X	±0.25	X.°	±3°		
0.XX	±0.12				
0.XXX	±0.05	X.X°	±0.5°		
UNIT	SIZE	SCALE	DRAWING NO.	SHEET	PROD. NAME
MM	A4	1:1	006-1080-003	1 OF 1	PHD-2XnAW-DKF
			TITLE	PART NO. 61080-**02-5001	
			2.0 WTB CONN. DIP DUAL ROW RIGHT-ANGLE		

借用登记

旧底图总号

底图总号

签字

日期